

you can  
**Canon**

**i-SENSYS**  
MF4330d

Laser Mono  
Multifunctional Printer

Compact, affordable and  
productive laser All-in-One

i-SENSYS MF4330d

Boost small office productivity with professional print, copy and scan quality, complete with automatic document feeding. This compact mono laser All-in-One is fast, energy efficient, easy to use and features automatic double-sided printing.



**22ppm**  
monochrome  
printing

**250-sheet**  
paper tray

**Virtually zero**  
warm-up time

**1200 x 600dpi**  
print resolution

**9600 x 9600dpi**  
Colour scanning

**Duplex**  
printing



### WHAT'S IN THE BOX

Main unit, cartridge FX10, power cable, USB cable, starter guide, manuals on CD, user software CD, warranty card.

### KEY FEATURES

- Compact laser All-in-One: print, copy and scan
- 22 ppm mono printing and copying
- No waiting with Quick First-Print technologies
- First Copy Out Time of 9 seconds or less
- Automatic double-sided printing
- Up to 1200 x 600 dpi print resolution
- Colour scanning: up to 9600 x 9600 dpi, save as PDF
- 35-sheet Automatic Document feeder
- 250-sheet paper tray
- Energy saving – only 3 watts in sleep mode
- Maintenance-free All-in-One Cartridge for continuous high quality output
- USB 2.0 Hi-speed interface

### DIMENSIONS (W x D x H)

390 x 432 x 455 mm

### SUPPORTED OS

**Windows** 2000/ XP/ Vista

**Mac OS X** version 10.2.8-10.5.x (Web distribution only)

**Linux** (Web distribution only. The print driver will be released in approx. Sept 2009)



PRINT



COPY



FAX



SCAN



- 1** Flatbed and ADF
- 2** 250-sheet tray
- 3** FX10 cartridge

## Specifications

Machine type Available functions	Mono Laser All-in-One Print, Copy and Scan
<b>PRINTER</b> Print speed Print method Print quality Print resolution Double sided printing Printer languages Print margins Toner saver mode	Up to 22 ppm (A4) Monochrome laser beam printing Up to 1200 x 600 dpi with Automatic Image Refinement 600 x 600 dpi Automatic UFRII-LT 6 mm-top and bottom, 5 mm-left and right Yes
<b>COPIER</b> Copy speed First Copy Output Time (FCOT) Copy resolution Copy modes Double sided copying Multiple copy Reduction / Enlargement Toner saver mode Other features	Up to 22 cpm (A4) Approx. 9 seconds or less Up to 600 x 600 dpi Text, Text/Photo, Text/Photo+, Photo 1-sided to 2-sided (Manual) Up to 99 copies 50-200% in 1% increments Yes Collate, 2 on 1
<b>SCANNER</b> Type Scan resolution Colour scanning depth Greyscales Compatibility Max. scan width	Colour Optical: Up to 600 x 1200 dpi Enhanced: Up to 9600 x 9600 dpi 24 bit/24 bit (input/output) 256 levels TWAIN, WIA 216 mm
<b>MEDIA HANDLING</b> Scanner type Paper input (Standard)  Paper output Media types  Media sizes	Flatbed and Automatic Document Feeder (ADF) 250-sheets tray 1-sheet manual feed slot 35-sheets ADF 100-sheets Plain paper, Heavy paper, Recycled paper, Transparency, Label, Envelop Tray: A4, B5, A5, Executive, Envelope (COM10, Monarch, DL, ISO-C5), LTR, LGL, Custom sizes: Width 76 to 216 mm; Length 127 to 356 mm Manual feed slot: A4, B5, A5, Executive, Envelope (COM10, Monarch, DL, ISO-C5), LTR, LGL, Custom sizes: Width 76 to 216 mm; Length 127 to 356 mm ADF: A4, A5, Legal, Letter, Custom (W x L): Max 216 x 356 mm; Min 105 x 148.5 mm

Media weights	Tray: 64 to 128 g/m <sup>2</sup> Manual feed slot: 64 to 163 g/m <sup>2</sup> ADF: 40 to 105 g/m <sup>2</sup>
<b>INTERFACE &amp; SOFTWARE</b> Interface type Operating System compatibility  Software and printer management	USB 2.0 Hi-speed Windows 2000/ XP/ Vista Mac OS X version 10.2.8- 10.5.x <sup>1</sup> Linux <sup>1,2</sup>  Omni Page SE, Presto! Page Manager, MF toolbox
<b>GENERAL FEATURES</b> Duty cycle Warm-up Time Memory Control panel Dimensions with trays (W x D x H) Installation space (W x D x H) Weight Operating environment  Power Source Power Consumption  Noise Levels	Max. 10,000 pages per month Approx. 10 seconds from power on 32 MB (shared) 16 characters x 2 lines backlit LCD  390 mm x 432 mm x 455 mm  390 mm x 813 mm x 588 mm Approx. 12.75 Kg Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation) 220-240 V (±10%), 50/60 Hz (±2 Hz) Maximum: Approx. less than 650 W Active: Approx. less than 650 W Standby: Approx. less than 9 W Sleep mode: Approx. 3 W Typical Electricity Consumption (TEC): 0.915 kWh/week Sound Pressure <sup>3</sup> Active: 63.5 dB(A) or less Standby: Inaudible
<b>CONSUMABLES</b> Cartridges	Cartridge FX10 (2,000 pages <sup>4</sup> )
All specifications subject to change without notice	
<sup>1</sup> Web distribution only	
<sup>2</sup> The print driver will be released in approx. Sept 2009	
<sup>3</sup> Declared noise emission in accordance with ISO 9296	
<sup>4</sup> Based on 5% coverage	



you can  
**Canon**

Canon Inc.  
www.canon.com

Canon Europa N.V.  
www.canon-europe.com

English-UK Edition  
© Canon Europa N.V., 2008 (0908)

Canon (UK) Ltd  
Woodhatch  
Reigate  
Surrey  
RH2 8BF  
Telephone No: 01737 220000  
Facsimile No: 01737 220022  
www.canon.co.uk

Canon Ireland  
Arena Road,  
Sandyford Industrial Estate  
Dublin 18, Ireland  
T: 01 2052400  
F: 01 2958141  
www.canon.ie