



Sometimes your desktop
is out of control.

Sometimes it's not.

Lexmark **X340 MFP**

Low cost, full functionality –
right on your desktop!

More productivity

Use the 50-page Automatic Document Feeder to fax, scan and copy documents with ease – and zip through print runs as fast as 25 ppm!

Up to 25 ppm

More simplicity

Send faxes in just seconds thanks to the multiple speed-dial shortcuts, and simplify maintenance tasks with the intuitive 2-line backlit display.

Desktop user

More scanning capabilities

Scan colour documents directly to various PC applications and file types, including Word, PowerPoint, PDF and even editable text formats.

Simplify your daily tasks

We make printing easy

LEXMARKTM

Lexmark X340 MFP

Don't get up! Now you can do it all from your desk.

Affordable and very easy to use, the Lexmark X340 is the ideal solution for budget-sensitive desktop users that demand high-speed mono laser printing, copying, faxing and colour scanning – all in a single, space-saving device.

Faxing, as easy as 1, 2, 3

Three seconds or less! That's how fast the Lexmark X340 can transmit a fax, thanks to its high-speed 33.6Kbps modem. Just load a stack of originals into the 50-sheet Automatic Document Feeder, press one of the 10 speed-dial buttons, and let the X340 go to work for you!

Multitalented colour scanning

With its wide flatbed scanner and adjustable lid, the Lexmark X340 is perfect for scanning bound materials, like open books and reports. Use the included software to digitise hardcopy text into editable form, and import colour images into a wide range of applications and file formats.

Print Technology

Laser, Monochrome

Function

Colour Scanning, Copying, Faxing, Printing

Print Speed (A4 mono)

Up to 25 ppm

Print Speed (Letter mono)

Up to 27 ppm

Time to First Page (Black)

As fast as 10 seconds

Copy Speed (A4, Black)

Up to 25 cpm

Time to First Copy (Black)

As fast as 12 seconds

Print Resolution, Black

600 x 600 dpi

Scanning Resolution

600 X 600 dpi (mono)

Processor

150 MHz

Memory, standard

64 MB

Memory network model, maximum

64 MB

Expandable Memory Options

No

Citrix MetaFrame

Microsoft Windows 2000 Server running Terminal Services with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0., Microsoft Windows Server 2003 running Terminal Server with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0, Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 4.0, Microsoft Windows Server 2003 running Terminal Server with Citrix Presentation Server 4.0, Microsoft Windows Server 2003 x64 Edition (Standard, Enterprise) running Terminal Server with Citrix Presentation Server 4.0

Microsoft Windows Operating Systems Supported

2000, XP, Server 2003, XP x64, Server 2003 running Terminal Services, 2000 Server running Terminal Services, Server 2003 x64 Edition, Server 2003 x64 Edition running Terminal Services

Paper Handling (Standard)

150-Sheet Output Bin, Single Sheet Exit, Single Sheet Manual Feed Slot, 250-Sheet Input Tray

Paper Handling Optional

550-Sheet Drawer

Paper Input Capacity (Standard)

250 pages at 80 gsm bond

Paper Input Capacity (Maximum)

800 pages at 80 gsm bond

Paper Output Capacity (Standard)

150 pages at 80 gsm bond

Paper Output Capacity (Maximum)

150 pages at 80 gsm bond

Copy/Fax/Scan (ADF) Paper Input Capacity

Up to 50 pages at 80 gsm bond

Envelope Capacity

1

Finishing Option

No

Number of Paper Inputs

1

Number of Paper Inputs, Maximum

2

Media Types Supported

Card Stock, Envelopes, Paper Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide

Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement

Standard Ports

USB 2.0 Specification Hi-Speed Certified

Optional Network Ports

Lexmark N4000e Fast Ethernet (Print Only), Lexmark N4050e 802.11g Wireless Print Server (Print Only), External MarkNet™ N7020e Gigabit Ethernet, External MarkNet™ N7000e Fast Ethernet (USB)

Printable Area

4.0 mm of the top, bottom, right and left edges (within)

Printer Languages (Standard)

PCL 5e Emulation, PCL 6 Emulation

Reduce / Enlarge Range

25–400 %

Scan Area, Maximum

216 x 355.6 mm

Modem Speed

33.6 Kbps

Packaged Size (mm - H x W x D)

550 x 590 x 495 mm

Size (mm - H x W x D)

521 x 530 x 394 mm

Weight (kg)

16.33 kg

Noise Level, Idle

27 dBA

Noise Level, Operating

51 dBA

Copier Noise Level, Operating

52 dBA

Scanner Noise Level, Operating

49 dBA

Product Guarantee

One Year OnSite Repair, Next Business Day response time.

Product Certifications

CSA, ICES Class A, BSMI Class A, VCCI Class A, FCC Class A, UL 60950-1, IEC 320-1, ECMA-74, CE Class A, CB IEC 60950 1, IEC 61000-3-2, -3-3, EN 55022, EN 55024, CISPIR 22 Class A, GS (TÜV)-EN 60950-1, SEMKO, UL AR, CS, TÜV Rh, N Mark, C-tick Class A, CCC Class A, RPC, PSB, MIC, EK - K60950

Specified Operating Environment

Temperature: 16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 2500 Meters (8,200 Feet)

Supplies

Ships with 1,5K* pages Return Programme toner cartridge.

2,5K* pages High Yield Return Programme toner cartridge (aftermarket). Regular cartridge is also available.

- Printers and supplies are designed for use in Europe, Middle East and Africa only.

* Average cartridge yield. Declared yield value in accordance with ISO/IEC 19752.

Cost saving & environmental features

Taiwan Green Mark
WEEE
RoHS



Lexmark believes that the environment is a critical component of responsible business management and clearly demonstrates it by implementing the "4R" strategy: Reduce, Recover, Reuse and Recycle. To learn more about these programmes please visit www.lexmark.com/recycle



With our innovative solutions and services, we help you PRINT smarter, MOVE information faster and MANAGE output more efficiently across your enterprise. Ask your local Lexmark representative for more information.

Specifications are subject to change without notice. Lexmark, Lexmark with diamond design is trademark of Lexmark International, Inc. registered in the United States and/or other countries. All other trademarks are the properties of their respective owners.

www.lexmark.co.uk

LEXMARK
TM